

## alarm box SHEVS OPEN



# AK 10.x - Manual / pneumatical release OPEN

- Alarm box with integrated release valve RTC (see hand release valves) for manual and pneumatical release of a CO<sub>2</sub> bottle. CO<sub>2</sub> bottle is not included in our supply (for CO<sub>2</sub> bottles, please refer to valves -> accessories).
  Pneumatical release by attached pneumatic release. Minimum release pressure 5bar.
- Sheet steel alarm box with lockable cover. Two keys included (lock characteristics 60-001, special lock design upon request). Cut out section in cover is covered with a glass sheet on the inside. Control elements are visible and can be operated in the case of an alarm by smashing the glass (Paint finish RAL 2011 (orange)).
- Spare bottle holder
- Pipes connected with bulkhead fitting for 6mm OD pipe. Also available with bulkhead fitting for 8mm OD pipe.
- Visual indications Operation and Malfunction
- Maximum operating pressure 80bar
- ◆ Temperature range: -5°C to +55°C
- Additional technical data and drawings see data sheet AK 10.x

**Important**: it is not possible to connect several alarm boxes in series or in parallel without additional circuitry elements. Please inquire for various options.

## Types:

#### Alarm box for $CO_2$ one-way bottles with $\frac{1}{2}$ UNF thread:

AK 10.3-OR-HPA-R: max. 150g, 200x350x130 (WxHxD) AK 10.5-OR-HPA-R: max. 500g, 200x500x130 (WxHxD) AK 10.7-OR-HPA-R: max. 750g, 200x650x130 (WxHxD) AK 10.9-OR-HPA-R: max. 1500g, 220x700x170 (WxHxD)

## Alarm box for CO<sub>2</sub> bottles with dip tube; M18x1,5 thread:

AK 10.5-OR-HPA-SR-R: max. 500g, 300x530x130 (WxHxD) AK 10.9-OR-HPA-SR-R: max. 1500g, 320x680x170 (WxHxD)

## **Options:**

**AK 10.x-RT-HPA:** Paint finish RAL 3000 (red). **Ø8:** all connections for pipe diameter 8mm

## Accessories:

Spare glass sheet for AK 10.x: RT-E-Blanko



Alarm box for  $CO_2$  one-way bottles without dip tube